

STANCE E+ 2 POWER



SPECS

FRAME	
SIZES	XS, S, M, L, XL
COLORS	Electric Red
FRAME	ALUXX SL-grade aluminum, 120mm FlexPoint suspension system
FORK	SR Suntour XCR 34 Air LO-R, 130mm travel, tapered steerer, Lockout, 110x15 Quick-Loc thru-axle
SHOCK	RockShox Monarch R, High Volume, 184x44mm, custom tuned
COMPONENTS	
HANDLEBAR	Giant Connect TR Riser 31.8x780mm
STEM	Giant Contact
SEATPOST	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SADDLE	Giant Contact, Neutral
PEDALS	-
DRIVETRAIN	
SHIFTERS	Shimano Deore
FRONT DERAILLEUR	-
REAR DERAILLEUR	Shimano Deore, 10-Speed, Shadow+
BRAKES	Tektro HD-M745 Orion, 4-piston, hydraulic disc, 203mm
BRAKE LEVERS	Tektro HD-M745 Orion
CASSETTE	Shimano HG500-10, 11-42T, 10-Speed
CHAIN	KMC e.10 Sport, e-bike optimized
CRANKSET	Forged Alloy minimal Q-factor, 36T Steel Direct Mount ring (XS/S:160, M/L:165, XL:170)
WHEELS	
BOTTOM BRACKET	N/A
RIMS	Giant AM 27.5+, Tubeless ready, 35mm inner width
HUBS	Giant eTracker Sport, [F] 15mm Thru-Axle [R] 141mm QR
SPOKES	Stainless Steel
TIRES	Maxxis Rekon 27.5x2.6", Exo protect, Tubeless Ready
EXTRAS	Giant EnergyPak 6A Smart charger
HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport
SENSORS	Giant PedalPlus 6-sensor technology
DISPLAY	Giant RideControl ONE
BATTERY	Giant EnergyPak Smart 500, 36V 13.8Ah integrated Lithium-Ion

FEATURES

- Frame: ALUXX SL-grade aluminum, 120mm FlexPoint suspension system
- Fork: SR Suntour XCR 34 Air LO-R, 130mm travel, tapered steerer, Lockout, 110x15 Quick-Loc thru-axle
- Shifters: Shimano Deore
- Crankset: Forged Alloy minimal Q-factor, 36T Steel Direct Mount ring (XS/S:160, M/L:165, XL:170)
- Colors: Electric Red

GEOMETRY

FRAME	XS	S	M	L	XL
Seat Tube Length (mm)	380	406	432	482	507
Seat Tube Angle	73.5°	73.5°	73.5°	73.5°	73.5°
Top Tube Length (mm)	565	580	600	625	650
Head Tube Length (mm)	100	100	110	120	135
Head Tube Angle	67.0°	67.0°	67.0°	67.0°	67.0°
Fork Rake (mm)	46	46	46	46	46
Trail (mm)	106.9	106.9	106.9	106.9	106.9
Wheelbase (mm)	1147	1162	1183	1209	1236
Chain Stay Length (mm)	465	465	465	465	465
Bottom Bracket Drop (mm)	20	20	20	20	20
Stack (mm)	590	590	599	608	622
Reach (mm)	390	405	422	444	465
Stand Over Height (mm)	715	731	746	778	781
Handlebar Width (mm)	780	780	780	780	780
Stem Length (mm)	50	50	60	60	70
Crank Length (mm)	165	165	170	170	170
Wheel Size	27.5+	27.5+	27.5+	27.5+	27.5+

The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city / country.