



SPECS

FRAME	
SIZES	XS, S, M, L
COLORS	Metallic Black
FRAME	ALUXX SL aluminum, Overdrive 1½ - 1⅝" head tube, 148x12mm Thru-Axle, integrated KS18 kickstand mount
FORK	Rock Shox Recon RL 120mm travel, Tapered 1½ - 1⅝" steerer, 110x15QR, lockout
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Connect TR Riser
STEM	Giant Contact
SEATPOST	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SADDLE	Liv Sport
PEDALS	-
DRIVETRAIN	
SHIFTERS	SRAM SX Eagle
FRONT DERAILLEUR	-
REAR DERAILLEUR	SRAM SX Eagle
BRAKES	Shimano MT400, Hydraulic Disc, 180/203mm
BRAKE LEVERS	Shimano MT401 Hydraulic Disc
CASSETTE	SRAM Eagle PG-1210, 11-50T, 12-Speed
CHAIN	SRAM SX Eagle
CRANKSET	SRAM X-Sync 38T chainring Forged Alloy minimal Q-factor
WHEELS	
BOTTOM BRACKET	N/A
RIMS	Giant AM 27.5+, Tubeless ready, 35mm inner width, e-bike optimized
HUBS	Giant eTracker Boost, Sealed cartridge bearing, 6-bolt, [F] 110x15 [R] 148x12mm Thru-axle, e-bike optimized
SPOKES	Sapim E-Lite [r] Race [f], e-bike optimized
TIRES	Maxxis Forekaster 27.5x2.6, foldable, 60 TPI, EXO, Tubeless Ready
EXTRAS	Giant EnergyPak 6A Smart charger Tubeless kit
HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro, 80Nm, 360% tuneable support, powered by YAMAHA
SENSORS	Giant PedalPlus 6-sensor technology
DISPLAY	Giant RideControl ONE, remote button
BATTERY	Giant EnergyPak 500, 36V 13.8Ah integrated Lithium-Ion

FEATURES

- Frame: ALUXX SL aluminum, Overdrive 1½ - 1⅝" head tube, 148x12mm Thru-Axle, integrated KS18 kickstand mount
- Fork: Rock Shox Recon RL 120mm travel, Tapered 1½ - 1⅝" steerer, 110x15QR, lockout
- Shifters: SRAM SX Eagle
- Crankset: SRAM X-Sync 38T chainring Forged Alloy minimal Q-factor
- Colors: Metallic Black

GEOMETRY

FRAME	XS	S	M	L
Seat Tube Length (mm)	365	405	460	510
Seat Tube Angle	74.0°	73.5°	73.0°	73.0°
Top Tube Length (mm)	560	565	585	600
Head Tube Length (mm)	110	115	135	150
Head Tube Angle	68.0°	68.0°	68.0°	68.0°
Fork Rake (mm)	42	42	42	42
Trail (mm)	103.8	103.8	103.8	103.8
Wheelbase (mm)	1131	1130	1146	1163
Chain Stay Length (mm)	475	475	475	475
Bottom Bracket Drop (mm)	50	50	50	50
Stack (mm)	624	628	647	661
Reach (mm)	381	378	387	398
Handlebar Width (mm)	690	690	750	750
Stem Length (mm)	50	50	60	70
Crank Length (mm)	170	170	170	170
Wheel Size	27.5+	27.5+	27.5+	27.5+

The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city / country.