

# EMBOLDEN E+ 2 POWER



## SPECS

FRAME	
SIZES	XS, S, M, L
COLORS	Navy Gray
FRAME	ALUXX SL-grade aluminum, 120mm FlexPoint suspension system
FORK	SR Suntour XCR 34 Air LO-R, 130mm travel, tapered steerer, Lockout, 110x15 Quick-Loc thru-axle
SHOCK	RockShox Monarch R, High Volume, 184x44mm, custom tuned
COMPONENTS	
HANDLEBAR	Giant Connect TR Riser
STEM	Giant Contact
SEATPOST	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SADDLE	Liv Contact upright
PEDALS	-
DRIVETRAIN	
SHIFTERS	Shimano Deore
FRONT DERAILLEUR	-
REAR DERAILLEUR	Shimano Deore, 10-Speed, Shadow+
BRAKES	Tektro HD-M745 Orion, 4-piston, hydraulic disc, 203mm
BRAKE LEVERS	Tektro HD-M745 Orion
CASSETTE	Shimano HG500-10, 11-42T, 10-Speed
CHAIN	KMC e.10 Sport, e-bike optimized
CRANKSET	Forged Alloy minimal Q-factor, 36T Steel Direct Mount ring (XS/S:160, M/L:165)
WHEELS	
BOTTOM BRACKET	N/A
RIMS	Giant AM 27.5+, Tubeless ready, 35mm inner width, e-bike optimized
HUBS	Giant eTracker Boost, Sealed Cartridge bearing, 15 6-bolt, [F] 110x15 [R] 141x9mm Quick-Release, e-bike optimized
SPOKES	Stainless Steel
TIRES	Maxxis Rekon 27.5x2.6", Exo protect, Tubeless Ready
EXTRAS	Giant EnergyPak 6A Smart charger
HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport, 70Nm, 350% tuneable support with automatic smart support
SENSORS	Giant PedalPlus 6-sensor technology
DISPLAY	Giant RideControl ONE, remote button
BATTERY	Giant EnergyPak Smart 500, 36V 13.8Ah integrated Lithium-Ion

## FEATURES

- Frame: ALUXX SL-grade aluminum, 120mm FlexPoint suspension system
- Fork: SR Suntour XCR 34 Air LO-R, 130mm travel, tapered steerer, Lockout, 110x15 Quick-Loc thru-axle
- Shifters: Shimano Deore
- Crankset: Forged Alloy minimal Q-factor, 36T Steel Direct Mount ring (XS/S:160, M/L:165)
- Colors: Navy Gray

## GEOMETRY

FRAME	XS	S	M	L
Seat Tube Length (mm)	380	406	445	490
Seat Tube Angle	74.0°	74.0°	74.0°	74.0°
Top Tube Length (mm)	565	580	595	610
Head Tube Length (mm)	100	100	110	120
Head Tube Angle	67.5°	67.5°	67.5°	67.5°
Fork Rake (mm)	46	46	46	46
Trail (mm)	103.3	103.3	103.3	103.3
Wheelbase (mm)	1147	1162	1178	1194
Chain Stay Length (mm)	465	465	465	465
Bottom Bracket Drop (mm)	20	20	20	20
Stack (mm)	592	592	602	611
Reach (mm)	395	410	422	435
Stand Over Height (mm)	710	728	756	789
Handlebar Width (mm)	750	750	780	780
Stem Length (mm)	40	40	50	50
Crank Length (mm)	165	165	170	170
Wheel Size	27.5+	27.5+	27.5+	27.5+

*The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city / country.*