

# EXPLORE E+ 1 PRO STA

**GIANT**



## SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro
DISPLAY	Giant RideControl EVO
BATTERY	Giant EnergyPak Smart 625, 36V Integrated Lithium-Ion
RAHMEN	
GRÖSSEN	S, M, L
FARBE	Rosewood
RAHMEN	ALUXX SL aluminum, Overdrive 1½ - 1⅝" head tube, integrated KS18 kickstand mount
GABEL	SR Suntour NCX D AIR LO 63mm travel 15AH
DÄMPFER	N/A
KOMPONENTEN	
LENKER	Giant Connect XC Riser 31.8x690mm
VORBAU	Giant Contact
SATTELSTÜTZE	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SATTEL	Selle Royal Vivo Ergo Moderate Unisex
PEDALE	Aluminium Plattform
ANTRIEB	
SCHALTHEBEL	Shimano Deore
UMWERFER	Shimano Deore
SCHALTWERK	Shimano Deore, 11-Speed, Shadow+
BREMSEN	Shimano BR-MT410, hydraulic disc, 180mm
BREMSHEBEL	Shimano BL-M4100, I-spec EV
KASSETTE	Shimano CS-M5100, 11-42T, 11-Speed
KETTE	KMC e.11 Sport, e-bike optimized
KURBEL	Forged Alloy minimal Q-factor, 36/48T
TRETLAGER	N/A
LAUFRÄDER	
FELGEN	Giant eX2, Tubeless Ready, 700c Aluminium
NABE	Giant eTracker, sealed cartridge bearings [F] 15mm Thru-Axle [R] 142x12 Thru-axle
SPEICHEN	Sapim E-Lite [r] Race [f], e-bike optimized
REIFEN	Giant Crosscut Gravel 2, 700x45c (622x45), Tubeless Ready, Reflex
EXTRAS	Giant EnergyPak Smart 6A charger Giant EnergyPak Plus range extender compatible
ACCESSORIES	
LIGHTING	Axa BlueLine 50Lux Steady E6 front Axa BlueLine Steady E6 rear
GEPÄCKTRÄGER	MIK rack. System bag & basket compatible

## MODELL-MERKMALE

- Rahmen: ALUXX SL aluminum, Overdrive 1½ - 1⅝" head tube, integrated KS18 kickstand mount
- Gabel: SR Suntour NCX D AIR LO 63mm travel 15AH
- Schalthebel: Shimano Deore
- Kurbel: Forged Alloy minimal Q-factor, 36/48T
- Farbe: Rosewood

## GEOMETRIEDATEN

RAHMEN	S	M	L
Sitzrohrlänge (mm)	435	485	535
Sitzrohrwinkel	73.0°	73.0°	73.0°
Oberrohrlänge (mm)	570	590	610
Steuerrohr-Länge (mm)	125	140	155
Steuerrohr-Winkel	69.5°	69.5°	69.5°
Gabelneigung (mm)	42	42	42
Trail (mm)	91.3	91.3	91.3
Radstand (mm)	1112	1121	1142
Kettenstreben-Länge (mm)	455	455	455
Tretlager-Höhe (mm)	60	60	60
Stack (mm)	591	605	619
Reach (mm)	380	385	400
Überstandshöhe (mm)	682	676	665
Lenkerbreite (mm)	690	690	690
Vorbaulänge (mm)	60	70	80
Kurbellänge (mm)	170	170	170
Radgrösse	700C	700C	700C

Spezifikations-, Preis- und Farbaenderungen vorbehalten.