



## SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
<b>MOTOR</b>	Giant SyncDrive Pro
<b>DISPLAY</b>	Giant New RideControl EVO
<b>BATTERY</b>	Giant EnergyPak Smart 625, 36V Integrated Lithium-Ion
RAHMEN	
<b>GRÖSSEN</b>	S, M, L, XL
<b>FARBE</b>	Gunmetal Black/Black
<b>RAHMEN</b>	ALUXX SL aluminum, Overdrive 1½ - 1⅝" head tube, 148x12mm Thru-Axle, integrated KS18 kickstand mount
<b>GABEL</b>	SR Suntour Raidon 34 Boost Air LOR, 130mm travel, Tapered 1½ - 1⅝" steerer, lockout
<b>DÄMPFER</b>	N/A
KOMPONENTEN	
<b>LENKER</b>	Giant Connect TR Riser 31.8x780mm
<b>VORBAU</b>	Giant Contact
<b>SATTELSTÜTZE</b>	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
<b>SATTEL</b>	Giant Sport
<b>PEDALE</b>	Aluminum Platform
ANTRIEB	
<b>SCHALTHEBEL</b>	Shimano Deore, 11-Speed
<b>UMWERFER</b>	-
<b>SCHALTWERK</b>	Shimano Deore, 11-Speed, Shadow+
<b>BREMSEN</b>	Shimano BR-MT200, hydraulic disc, 180mm [F&R]
<b>BREMSHEBEL</b>	Shimano BL-MT200
<b>KASSETTE</b>	Shimano CS-M5100 11-51T 11-Speed
<b>KETTE</b>	KMC e11 Sport EPT e-bike optimized
<b>KURBEL</b>	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set
<b>TRETLAGER</b>	N/A
LAUFRÄDER	
<b>FELGEN</b>	Giant XCT 29 Tubeless Ready 25mm e-bike optimized
<b>NABE</b>	Giant eTracker Boost, Sealed cartridge bearing, 6-bolt, [F] 110x15 [R] 148x12mm Thru-axle
<b>SPEICHEN</b>	Stainless steel
<b>REIFEN</b>	Maxxis DHF 29X2.5" WT Foldable 60TPI TLR EXO [F] Maxxis Aggressor 29X2.5" WT Foldable 60TPI TLR EXO [R]
<b>EXTRAS</b>	Giant EnergyPak Smart 6A charger

## MODELL-MERKMALE

- Rahmen: ALUXX SL aluminum, Overdrive 1½ - 1⅝" head tube, 148x12mm Thru-Axle, integrated KS18 kickstand mount
- Gabel: SR Suntour Raidon 34 Boost Air LOR, 130mm travel, Tapered 1½ - 1⅝" steerer, lockout
- Schalthebel: Shimano Deore, 11-Speed
- Kurbel: Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set
- Farbe: Gunmetal Black/Black

## GEOMETRIEDATEN

RAHMEN	S	M	L	XL
Sitzrohrlänge (mm)	405	455	505	535
Sitzrohrwinkel	76.0°	76.0°	76.0°	76.0°
Oberrohrlänge (mm)	575	600	625	650
Steuerrohr-Länge (mm)	105	115	125	135
Steuerrohr-Winkel	66.0°	66.0°	66.0°	66.0°
Gabelneigung (mm)	51	51	51	51
Trail (mm)	108.5	108.5	108.5	108.5
Radstand (mm)	1204	1231	1258	1285
Kettenstreben-Länge (mm)	475	475	475	475
Tretlager-Höhe (mm)	45	45	45	45
Stack (mm)	616	625	635	644
Reach (mm)	421	444	467	490
Überstandshöhe (mm)	758	762	794	816
Lenkerbreite (mm)	780	780	780	780
Vorbaulänge (mm)	50	60	60	70
Kurbellänge (mm)	165	170	170	170
Radgrösse	29"	29"	29"	29"

Spezifikations-, Preis- und Farbaenderungen vorbehalten.