



## SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, ML, L, XL
FARBE	Concrete
RAHMEN	Advanced-Grade Composite, 12x142mm thru-axle, disc
GABEL	Advanced-Grade Composite, full-composite OverDrive steerer, 12mm thru-axle, disc
DÄMPFER	N/A
KOMponenten	
LENKER	Giant Contact XR D-Fuse, 31.8
VORBAU	Giant Contact, 8-degree
SATTELSTÜTZE	Giant D-Fuse, composite
SATTEL	Giant Approach
PEDALE	N/A
ANTRIEB	
SCHALTHEBEL	Shimano GRX RX-600
UMWERFER	N/A
SCHALTWERK	Shimano GRX RX-810
BREMSEN	Shimano GRX RX-400 hydraulic
BREMSHEBEL	Shimano GRX RX-600 hydraulic
KASSETTE	Shimano CS-M7000, 11x42
KETTE	KMC X11EL-1
KURBEL	Shimano FC-RX600, 40t
TRETLAGER	Shimano, press fit
LAUFRÄDER	
FELGEN	Giant P-X2 Disc wheelset
NABE	Giant P-X2 Disc wheelset
SPEICHEN	Giant P-X2 Disc wheelset
REIFEN	Giant CrossCut AT 1 Tubeless, 700x38C

## MODELL-MERKMALE

- Rahmen: Advanced-Grade Composite, 12x142mm thru-axle, disc
- Gabel: Advanced-Grade Composite, full-composite OverDrive steerer, 12mm thru-axle, disc
- Schalthebel: Shimano GRX RX-600
- Kurbel: Shimano FC-RX600, 40t
- Farbe: Concrete

## GEOMETRIEDATEN

RAHMEN	XS	S	M	ML	L	XL
Sitzrohrlänge (mm)	430	450	470	490	510	530
Sitzrohrwinkel	74.0°	73.5°	73.5°	73.0°	73.0°	73.0°
Oberrohrlänge (mm)	530	540	550	565	575	590
Steuerrohr-Länge (mm)	125	135	150	165	180	195
Steuerrohr-Winkel	70.5°	70.5°	70.5°	71.0°	71.0°	71.0°
Gabelneigung (mm)	50	50	50	50	50	50
Trail (mm)	74.1	74.1	74.1	70.7	70.7	70.7
Radstand (mm)	1014	1020	1031	1036	1046	1062
Kettenstreben-Länge (mm)	425	425	425	425	425	425
Tretlager-Höhe (mm)	70	70	70	70	70	70
Stack (mm)	548	558	572	588	602	616
Reach (mm)	373	375	381	385	391	402
Überstandshöhe (mm)	719	734	752	768	786	803
Lenkerbreite (mm)	420	420	440	440	460	460
Vorbaulänge (mm)	70	80	90	100	100	100
Kurbellänge (mm)	170	170	172.5	172.5	175	175
Radgrösse	700C	700C	700C	700C	700C	700C

Spezifikations-, Preis- und Farbaenderungen vorbehalten.