



SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport
DISPLAY	Giant RideControl Plus
BATTERY	Giant EnergyPak Smart 625, 36V Integrated Lithium-Ion
RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Desert Sage
RAHMEN	ALUXX SL-grade aluminum, 120mm FlexPoint suspension system
GABEL	RockShox Recon Silver RL, 130mm travel, Lockout, 110x15mm Boost, Maxle Stealth, e-MTB optimized
DÄMPFER	RockShox Monarch RT, High Volume, 184x44mm, custom tuned
KOMPONENTEN	
LENKER	Giant Connect TR Riser 31.8x780mm
VORBAU	Giant Contact
SATTELSTÜTZE	Giant Contact Switch, dropper, 30,9mm (S:125/M:150/L&XL:170)
SATTEL	Giant Sport
PEDALE	Aluminum Platform
ANTRIEB	
SCHALTHEBEL	SRAM SX Eagle 12-speed
UMWERFER	MRP 1X CS custom
SCHALTWERK	SRAM SX Eagle 12-speed
BREMSEN	Shimano MT420, 4-piston, hydraulic disc, 203mm
BREMSEBEL	Shimano MT401
KASSETTE	SRAM PG-1210, 11-50T, 12-Speed
KETTE	SRAM SX Eagle PowerLock, 12-speed
KURBEL	SRAM X-Sync Eagle 38T 104BCD chainring Forged Alloy minimal Q-factor, (S:160, M/L:165, XL:170)
TRETLAGER	N/A
LAUFRÄDER	
FELGEN	Giant XCT 29 Tubeless Ready 25mm e-bike optimized
NABE	Giant eTracker Sport, [F] 15mm Thru-Axle [R] 141mm QR
SPEICHEN	Stainless Steel
REIFEN	Maxxis Rekon 29x2.4" foldable, 60tpi, EXO, Tubeless Ready
EXTRAS	Giant EnergyPak 6A Smart charger

MODELL-MERKMALE

- Rahmen: ALUXX SL-grade aluminum, 120mm FlexPoint suspension system
- Gabel: RockShox Recon Silver RL, 130mm travel, Lockout, 110x15mm Boost, Maxle Stealth, e-MTB optimized
- Schalthebel: SRAM SX Eagle 12-speed
- Kurbel: SRAM X-Sync Eagle 38T 104BCD chainring Forged Alloy minimal Q-factor, (S:160, M/L:165, XL:170)
- Farbe: Desert Sage

GEOMETRIEDATEN

RAHMEN	S	M	L	XL
Sitzrohrlänge (mm)	406	432	482	507
Sitzrohrwinkel	73.5°	73.5°	73.5°	73.5°
Oberrohrlänge (mm)	580	600	625	650
Steuerrohr-Länge (mm)	100	110	120	135
Steuerrohr-Winkel	67.0°	67.0°	67.0°	67.0°
Gabelneigung (mm)	40	40	40	40
Trail (mm)	113.6	113.6	113.6	113.6
Radstand (mm)	1166	1187	1213	1240
Kettenstreben-Länge (mm)	475	475	475	475
Tretlager-Höhe (mm)	20	20	20	20
Stack (mm)	593	603	612	626
Reach (mm)	404	421	444	465
Überstandshöhe (mm)	741	756	788	792
Lenkerbreite (mm)	780	780	780	780
Vorbaulänge (mm)	40	40	50	50
Kurbellänge (mm)	160	160	165	165
Radgrösse	29"	29"	29"	29"

Spezifikations-, Preis- und Farbaenderungen vorbehalten.