



SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport
BATTERY	Giant EnergyPak Smart 500, 36V Integrated Lithium-Ion
RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Ocean Storm
RAHMEN	ALUXX SL-grade aluminum, 120mm FlexPoint suspension system
GABEL	SR Suntour XCR 34 Air LO-R, 130mm travel, tapered steerer, Lockout, 110x15 Quick-Loc thru-axle
DÄMPFER	RockShox Monarch R, High Volume, 184x44mm, custom tuned
KOMPONENTEN	
LENKER	Giant Connect TR Riser 31.8x780mm
VORBAU	Giant Contact
SATTELSTÜTZE	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SATTEL	Giant Sport
PEDALE	Aluminum Platform
ANTRIEB	
SCHALTHEBEL	Shimano Deore
UMWERFER	MRP 1X CS custom
SCHALTWERK	Shimano Deore, 10-Speed, Shadow+
BREMSEN	Tektro HD-M745 Orion, 4-piston, hydraulic disc, 203mm
BREMSHEBEL	Tektro HD-M745 Orion
KASSETTE	Shimano CS-M4100-10, 11-46T, 10-Speed
KETTE	KMC e.10 Sport, e-bike optimized
KURBEL	Forged Alloy minimal Q-factor, 36T Steel Direct Mount ring (S:160, M/L:165, XL:170)
TRETLAGER	N/A
LAUFRÄDER	
FELGEN	Giant XCT 29 Tubeless Ready 25mm e-bike optimized
NABE	Giant eTracker Sport, [F] 15mm Thru-Axle [R] 141mm QR
SPEICHEN	Stainless Steel
REIFEN	Maxxis Rekon 29x2.25" foldable, 60tpi, EXO, Tubeless Ready
EXTRAS	Giant EnergyPak 6A Smart charger
ACCESSORIES	
LIGHTING	Herrmans H-BLACK MR8
GEPÄCKTRÄGER	Giant Rack-It MIK

MODELL-MERKMALE

- Rahmen: ALUXX SL-grade aluminum, 120mm FlexPoint suspension system
- Gabel: SR Suntour XCR 34 Air LO-R, 130mm travel, tapered steerer, Lockout, 110x15 Quick-Loc thru-axle
- Schalthebel: Shimano Deore
- Kurbel: Forged Alloy minimal Q-factor, 36T Steel Direct Mount ring (S:160, M/L:165, XL:170)
- Farbe: Ocean Storm

GEOMETRIEDATEN

RAHMEN	S	M	L	XL
Sitzrohrlänge (mm)	406	432	482	507
Sitzrohrwinkel	73.5°	73.5°	73.5°	73.5°
Oberrohrlänge (mm)	580	600	625	650
Steuerrohr-Länge (mm)	100	110	120	135
Steuerrohr-Winkel	67.0°	67.0°	67.0°	67.0°
Gabelneigung (mm)	40	40	40	40
Trail (mm)	113.6	113.6	113.6	113.6
Radstand (mm)	1166	1187	1213	1240
Kettenstreben-Länge (mm)	475	475	475	475
Tretlager-Höhe (mm)	20	20	20	20
Stack (mm)	593	603	612	626
Reach (mm)	404	421	444	465
Überstandshöhe (mm)	741	756	788	792
Lenkerbreite (mm)	780	780	780	780
Vorbaulänge (mm)	40	40	50	50
Kurbellänge (mm)	160	160	165	165
Radgrösse	29"	29"	29"	29"

Spezifikations-, Preis- und Farbaenderungen vorbehalten.