

# STANCE E+ 1 PRO

GIANT



## SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro
DISPLAY	Giant RideControl EVO (New)
BATTERY	Giant EnergyPak Smart 625, 36V 17.3Ah integrated Lithium-Ion
RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Metallic Black
RAHMEN	ALUXX SL-grade aluminum, 120mm FlexPoint suspension system
GABEL	RockShox Recon Silver RL, 130mm travel, Lock-out, Tapered Steerer, 15x110mm Boost, MaxleLite, e-MTB optimized
DÄMPFER	RockShox Monarch RT, High Volume, 184x44mm, custom tuned
KOMPONENTEN	
LENKER	Giant Connect TR Riser 31.8x780mm
VORBAU	Giant Contact
SATTELSTÜTZE	Giant Contact Switch, dropper, 30,9mm (S:100/M:125/L:150/XL:170)
SATTEL	Giant Romero Trail
PEDALE	Flatpedal
ANTRIEB	
SCHALTHEBEL	Shimano Deore 12-speed I-spec EV
UMWERFER	MRP 1X custom "V3" co-molded TR chain guide
SCHALTWERK	Shimano Deore 12-speed
BREMSEN	Shimano BR-MT420, 4-piston, hydraulic disc, 203mm
BREMSEBEL	Shimano Deore BL-M4100 I-spec EV
KASSETTE	Shimano CS-M6100-12, 10-51T, 12-speed
KETTE	KMC e.12 Turbo, EcoProteq, e-bike optimized
KURBEL	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (Q-factor=168, S:160, M/L:165, XL:170)
TRETLAGER	N/A
LAUFRÄDER	
FELGEN	Giant XCT 29 Tubeless Ready 25mm e-bike optimized
NABE	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
SPEICHEN	Sapim E-Lite [R] Race [F], e-bike optimized
REIFEN	Maxxis Minion DHF 29X2.5" 60TPI Foldable, TLR EXO [F] Maxxis Minion DHR II 29X2.40 60TPI Foldable TLR EXO [R]
EXTRAS	Giant EnergyPak Smart 6A charger Tubeless kit (liquid, valves, levers, manual, tool)

## MODELL-MERKMALE

- Rahmen: ALUXX SL-grade aluminum, 120mm FlexPoint suspension system
- Gabel: RockShox Recon Silver RL, 130mm travel, Lock-out, Tapered Steerer, 15x110mm Boost, MaxleLite, e-MTB optimized
- Schalthebel: Shimano Deore 12-speed I-spec EV
- Kurbel: Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (Q-factor=168, S:160, M/L:165, XL:170)
- Farbe: Metallic Black

## GEOMETRIEDATEN

RAHMEN	S	M	L	XL
Sitzrohrlänge (mm)	406	432	482	507
Sitzrohrwinkel	73.5°	73.5°	73.5°	73.5°
Oberrohrlänge (mm)	580	600	625	650
Steuerrohr-Länge (mm)	100	110	120	135
Steuerrohr-Winkel	67.0°	67.0°	67.0°	67.0°
Gabelneigung (mm)	40	40	40	40
Trail (mm)	113.6	113.6	113.6	113.6
Radstand (mm)	1166	1187	1213	1240
Kettenstreben-Länge (mm)	475	475	475	475
Tretlager-Höhe (mm)	20	20	20	20
Stack (mm)	593	603	612	626
Reach (mm)	404	421	444	465
Überstandshöhe (mm)	741	756	788	792
Lenkerbreite (mm)	780	780	780	780
Vorbaulänge (mm)	40	40	50	50
Kurbellänge (mm)	160	160	165	165
Radgrösse	29"	29"	29"	29"

Spezifikations-, Preis- und Farbaenderungen vorbehalten.