

# TCR ADVANCED SL 0 DISC

**GIANT**



## SPEZIFIKATIONEN

| RAHMEN       |   |
|--------------|---|
| GRÖSSEN      | XS, S, M, ML, L, XL   |
| FARBE        | Matte Raw Carbon / Gloss Unicorn White                                |
| RAHMEN       | Advanced SL-Grade Composite, integrated seatpost, disc                |
| GABEL        | Advanced SL-Grade Composite, full-composite OverDrive 2 steerer, disc |
| DÄMPFER      | N/A   |
| KOMPONENTEN  |   |
| LENKER       | Giant Contact SLR   |
| VORBAU       | Giant Contact SLR   |
| SATTELSTÜTZE | integrated design   |
| SATTEL       | Giant Fleet SLR   |
| PEDALE       | N/A   |
| ANTRIEB      |   |
| SCHALTHEBEL  | SRAM RED eTap AXS   |
| UMWERFER     | SRAM RED eTap AXS   |
| SCHALTWERK   | SRAM RED eTap AXS   |
| BREMSEN      | SRAM RED eTap AXS hydraulic   |
| BREMSEBEL    | SRAM RED eTap AXS hydraulic   |
| KASSETTE     | SRAM RED, 12-speed, 10x28   |
| KETTE        | SRAM RED D1   |
| KURBEL       | SRAM RED D1 DUB, 35/48with Quarq DZero power meter                    |
| TRETLAGER    | SRAM DUB, press fit   |
| LAUFRÄDER    |   |
| FELGEN       | CADEX 42mm Disc WheelSystem (F:42mm, R:42mm)                          |
| NABE         | CADEX 42mm Disc WheelSystem, 12mm thru-axle                           |
| SPEICHEN     | CADEX 42mm Disc WheelSystem   |
| REIFEN       | CADEX Road Race, tubeless, 700x28mm (25c), folding                    |
| EXTRAS       | computer mount  |

## MODELL-MERKMALE

- Rahmen: Advanced SL-Grade Composite, integrated seatpost, disc
- Gabel: Advanced SL-Grade Composite, full-composite OverDrive 2 steerer, disc
- Schalthebel: SRAM RED eTap AXS
- Kurbel: SRAM RED D1 DUB, 35/48with Quarq DZero power meter
- Farbe: Matte Raw Carbon / Gloss Unicorn White

## GEOMETRIEDATEN

| RAHMEN                   | XS    | S     | M     | ML    | L     | XL    |
|--------------------------|-------|-------|-------|-------|-------|-------|
| Sitzrohrlänge (mm)       | 680   | 710   | 740   | 770   | 800   | 830   |
| Sitzrohrwinkel           | 74.5° | 74.0° | 73.5° | 73.0° | 73.0° | 72.5° |
| Oberrohrlänge (mm)       | 520   | 535   | 550   | 565   | 580   | 600   |
| Steuerrohr-Länge (mm)    | 120   | 130   | 145   | 165   | 185   | 200   |
| Steuerrohr-Winkel        | 71.0° | 72.3° | 73.0° | 73.0° | 73.0° | 73.0° |
| Gabelneigung (mm)        | 45    | 45    | 45    | 45    | 45    | 45    |
| Trail (mm)               | 72.1  | 64    | 59.2  | 59.2  | 59.2  | 59.2  |
| Radstand (mm)            | 976   | 977   | 980   | 991   | 1006  | 1020  |
| Kettenstreben-Länge (mm) | 405   | 405   | 405   | 405   | 405   | 405   |
| Tretlager-Höhe (mm)      | 72    | 69.5  | 69.5  | 67    | 67    | 67    |
| Stack (mm)               | 517   | 528   | 545   | 562   | 581   | 596   |
| Reach (mm)               | 376   | 383   | 388   | 393   | 402   | 412   |
| Überstandshöhe (mm)      | 706   | 725   | 747   | 773   | 800   | 816   |
| Lenkerbreite (mm)        | 400   | 400   | 420   | 420   | 440   | 440   |
| Vorbaulänge (mm)         | 80    | 90    | 100   | 110   | 110   | 120   |
| Kurbellänge (mm)         | 170   | 170   | 172.5 | 172.5 | 175   | 175   |
| Radgrösse                | 700C  | 700C  | 700C  | 700C  | 700C  | 700C  |

Spezifikations-, Preis- und Farbaenderungen vorbehalten.