

# TRANCE X ADVANCED PRO 29 0

**GIANT**



## SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Chrysocolla/Astral Aura/Chrome
RAHMEN	Advanced-Grade Composite front and rear triangles, 135mm Maestro suspension, flip chip
GABEL	Fox 36 Factory Live Valve, FIT4, 44mm offset, 150mm, 15x110 Kabolt, custom tuned for Giant
DÄMPFER	Fox Float DPX2 Factory Live Valve, 185/55, custom tuned for Giant
KOMPONENTEN	
LENKER	Giant Contact SLR TR35, 780x35mm, 20mm rise
VORBAU	Giant Contact SL 35
SATTELSTÜTZE	Fox Transfer Factory dropper with Shimano remote, 30.9
SATTEL	Giant Romero SL
PEDALE	platform
ANTRIEB	
SCHALTHEBEL	Shimano Deore XT
UMWERFER	N/A
SCHALTWERK	Shimano Deore XTR
BREMSEN	Shimano Deore XT
BREMSHEBEL	Shimano Deore XT
KASSETTE	Shimano Deore XT, 10x51
KETTE	Shimano
KURBEL	Shimano Deore XT, 30t with MRP AMG V2 Carbon guide
TRETLAGER	Shimano, press fit
LAUFRÄDER	
FELGEN	Giant TRX-1 29 WheelSystem
NABE	Giant TRX-1 29 WheelSystem
SPEICHEN	Giant TRX-1 29 WheelSystem
REIFEN	[F] Maxxis Minion DHF 29x2.5, 3C, Max Terra, EXO, TR [R] Maxxis Dissector 29x2.4, 3C, Max Terra, EXO, TR, tubeless
EXTRAS	tubeless prepared

## MODELL-MERKMALE

- Rahmen: Advanced-Grade Composite front and rear triangles, 135mm Maestro suspension, flip chip
- Gabel: Fox 36 Factory Live Valve, FIT4, 44mm offset, 150mm, 15x110 Kabolt, custom tuned for Giant
- Schalthebel: Shimano Deore XT
- Kurbel: Shimano Deore XT, 30t with MRP AMG V2 Carbon guide
- Farbe: Chrysocolla/Astral Aura/Chrome

## GEOMETRIEDATEN

RAHMEN	S	M	L	XL
Sitzrohrlänge (mm)	LOW   HIGH	LOW   HIGH	LOW   HIGH	LOW   HIGH
Sitzrohrwinkel	77.2°   77.9°	77.2°   77.9°	77.2°   77.9°	77.2°   77.9°
Oberrohrlänge (mm)	566   564	597   595	629   627	656   654
Steuerrohr-Länge (mm)	95	100	110	120
Steuerrohr-Winkel	65.5°   66.2°	65.5°   66.2°	65.5°   66.2°	65.5°   66.2°
Gabelneigung (mm)	44	44	44	44
Trail (mm)	125.1   119.5	125.1   119.5	125.1   119.7	125.1   119.5
Radstand (mm)	1173   1171	1205   1203	1239   1238	1268   1266
Kettenstreben-Länge (mm)	438   435	438   435	438   435	438   435
Tretlager-Höhe (mm)	40   30	40   30	40   30	40   30
Stack (mm)	617   611	621   615	631   624	640   634
Reach (mm)	426   434	456   464	486   494	510   519
Überstandshöhe (mm)	729   738	729   737	752   761	760   770
Lenkerbreite (mm)	800	800	800	800
Vorbaulänge (mm)	40	40	50	50
Kurbellänge (mm)	165	170	170	170
Radgrösse	29"	29"	29"	29"

Spezifikations-, Preis- und Farbaenderungen vorbehalten.