



## SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport
DISPLAY	Giant RideControl Plus (optional)
BATTERY	Giant EnergyPak Smart 500, 36V Integrated Lithium-Ion
RAHMEN	
GRÖSSEN	XS, S, M, L (XS-S: 27.5", M-L: 29")
FARBE	Ocean Storm
RAHMEN	ALUXX SL-Grade Aluminum, 120mm FlexPoint Suspension System
GABEL	SR Suntour XCR 34 Air LO-R, 130mm travel, tapered steerer, Lockout, 110x15 Quick-Loc thru-axle
DÄMPFER	RockShox Monarch R, High Volume, 184x44mm, custom tuned
KOMPONENTEN	
LENKER	Giant Connect TR Riser 31.8x750-780mm (XS-S: 750 / M-L: 780)
VORBAU	Giant Contact
SATTELSTÜTZE	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SATTEL	Liv Contact Upright
PEDALE	Flatpedal
ANTRIEB	
SCHALTHEBEL	Shimano Deore
UMWERFER	-
SCHALTWERK	Shimano Deore, 10-Speed, Shadow+
BREMSEN	Tektro HD-M745 Orion, 4-piston, hydraulic disc, 203mm
BREMSEBEL	Tektro HD-M745 Orion
KASSETTE	Shimano CS-M4100-10, 11-46T, 10-Speed
KETTE	KMC e.10 Sport, e-bike optimized
KURBEL	Forged Alloy minimal Q-factor, 36T Steel Direct Mount ring (XS/S:160, M/L:165)
TRETLAGER	N/A
LAUFRÄDER	
FELGEN	Giant XCT 29 Tubeless Ready 25mm e-bike optimized
NABE	Giant eTracker Sport, [F] 15mm Thru-Axle [R] 141mm QR
SPEICHEN	Stainless Steel
REIFEN	Maxxis Rekon 29x2.4/ 27.5x2.4 Foldable, 60TP, EXO, Tubeless Ready (XS-S: 27.5", M-L: 29")
EXTRAS	Giant EnergyPak 6A Smart charger

## MODELL-MERKMALE

- Rahmen: ALUXX SL-Grade Aluminum, 120mm FlexPoint Suspension System
- Gabel: SR Suntour XCR 34 Air LO-R, 130mm travel, tapered steerer, Lockout, 110x15 Quick-Loc thru-axle
- Schalthebel: Shimano Deore
- Kurbel: Forged Alloy minimal Q-factor, 36T Steel Direct Mount ring (XS/S:160, M/L:165)
- Farbe: Ocean Storm

## GEOMETRIEDATEN

RAHMEN	XS	S	M	L
Sitzrohrlänge (mm)	380	406	445	490
Sitzrohrwinkel	74.0°	74.0°	74.0°	74.0°
Oberrohrlänge (mm)	565	580	595	610
Steuerrohr-Länge (mm)	100	100	110	120
Steuerrohr-Winkel	67.5°	67.5°	67.5°	67.5°
Gabelneigung (mm)	46	46	46	46
Trail (mm)	103.5	103.5	103.5	103.5
Radstand (mm)	1157	1172	1188	1204
Kettenstreben-Länge (mm)	475	475	475	475
Tretlager-Höhe (mm)	20	20	20	20
Stack (mm)	594	594	603	612
Reach (mm)	395	410	422	434
Überstandshöhe (mm)	710	738	765	786
Lenkerbreite (mm)	750	750	780	780
Vorbaulänge (mm)	40	40	50	60
Kurbellänge (mm)	160	165	165	170
Radgrösse	27.5+	29"	29"	29"

Spezifikations-, Preis- und Farbaenderungen vorbehalten.