

# INTRIGUE ADVANCED PRO 29 0



## SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S, M, L
FARBE	Supernova
RAHMEN	Advanced-Grade Composite front and rear triangles, 125mm Maestro Suspension, flip chip
GABEL	Fox 36 Factory Live Valve, 140mm, FIT4 damper, Boost, 15x110, Kabolt, tapered, 44mm offset, custom tuned for Liv
DÄMPFER	Fox Float DPX2 Factory Live Valve [185/50], custom tuned for Liv
KOMPONENTEN	
LENKER	Giant Contact SLR TR35, 780x35
VORBAU	Giant Contact SL 35
SATTELSTÜTZE	Fox Transfer Factory dropper, Shimano remote lever, 30.9
SATTEL	Liv Sylvia SL
PEDALE	N/A
ANTRIEB	
SCHALTHEBEL	Shimano Deore XT
UMWERFER	N/A
SCHALTWERK	Shimano XTR
BREMSEN	Shimano Deore XT
BREMSHEBEL	Shimano Deore XT
KASSETTE	Shimano Deore XT, 10x51
KETTE	Shimano
KURBEL	Shimano Deore XT, 30t with MRP AMg V2 carbon guide
TRETLAGER	Shimano, press fit
LAUFRÄDER	
FELGEN	Giant TRX-1 29 WheelSystem
NABE	Giant TRX-1 29 WheelSystem
SPEICHEN	Giant TRX-1 29 WheelSystem
REIFEN	[F] Maxxis Minion DHF 29x2.5WT, 3C Max Terra, EXO, TR, tubeless [R] Maxxis Dissector 29x2.4WT, 3C Max Terra, EXO, TR, tubeless
EXTRAS	tubeless prepared

## MODELL-MERKMALE

- Rahmen: Advanced-Grade Composite front and rear triangles, 125mm Maestro Suspension, flip chip
- Gabel: Fox 36 Factory Live Valve, 140mm, FIT4 damper, Boost, 15x110, Kabolt, tapered, 44mm offset, custom tuned for Liv
- Schalthebel: Shimano Deore XT
- Kurbel: Shimano Deore XT, 30t with MRP AMg V2 carbon guide
- Farbe: Supernova

## GEOMETRIEDATEN

RAHMEN	S	M	L
	LOW   HIGH	LOW   HIGH	LOW   HIGH
Sitzrohrlänge (mm)	425	435	460
Sitzrohrwinkel	77.0°   77.8°	77.0°   77.8°	77.0°   77.8°
Oberrohrlänge (mm)	558   557	574   573	599   597
Steuerrohr-Länge (mm)	105	110	125
Steuerrohr-Winkel	65.8°   66.5°	65.8°   66.5°	65.8°   66.5°
Gabelneigung (mm)	44	44	44
Trail (mm)	122   117	122   117	122   117
Radstand (mm)	1160   1160	1177   1176	1205   1204
Kettenstreben-Länge (mm)	438   435	438   435	438   435
Tretlager-Höhe (mm)	40   30	40   30	40   30
Stack (mm)	620   614	625   618	639   632
Reach (mm)	415   424	430   438	451   460
Überstandshöhe (mm)	742   751	732   741	751   759
Lenkerbreite (mm)	760	760	780
Vorbaulänge (mm)	50	50	50
Kurbellänge (mm)	170	170	175
Radgrösse	29"	29"	29"

Spezifikations-, Preis- und Farbaenderungen vorbehalten.