

EXPLORE E+ 2 GTS



SPECS

FRAME	
SIZES	S, M, L, XL
COLORS	Matte Black / Red
FRAME	ALUXX SL aluminum, Overdrive 1½ - 1⅝" head tube, integrated KS18 kickstand mount
FORK	RST Volante TNL coil, 60mm travel, tapered steerer, hydraulic lockout
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Connect XC Riser 31.8x690mm
STEM	Giant Contact
SEATPOST	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SADDLE	Selle Royal Vivo GTS/WMN
PEDALS	Aluminum Platform
DRIVETRAIN	
SHIFTERS	Shimano SL-M2000
FRONT DERAILLEUR	Shimano FD-M371
REAR DERAILLEUR	Shimano Deore
BRAKES	Shimano BR-MT200, hydraulic disc, 180mm
BRAKE LEVERS	Shimano BL-MT200
CASSETTE	Shimano CS-HG200, 11-36T, 9-Speed
CHAIN	KMC e.9 Sport, e-bike optimized
CRANKSET	Forged Alloy minimal Q-factor, 36/48T
WHEELS	
BOTTOM BRACKET	N/A
RIMS	Giant eX 2, Tubeless Ready, 700c aluminium
HUBS	Giant eTracker, [F] 100x9mm QR [R] 135mm QR
SPOKES	Stainless steel
TIRES	Giant Crosscut Gravel 2, 700x45c (622x45), Tubeless Ready, Reflex
EXTRAS	Giant EnergyPak 4A fast charger MIK system carrier top-deck
HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport
SENSORS	Giant PedalPlus 6-sensor technology
DISPLAY	Giant RideControl Charge
BATTERY	Giant EnergyPak 500, 36V 13.8Ah Rechargeable Lithium-Ion
ACCESSORIES	
LIGHTING	Axa BlueLine 30Lux Steady E6 front Axa BlueLine Steady E6 rear
LOCK	-
CARRIER	MIK rack. System bag & basket compatible

FEATURES

- Frame: ALUXX SL aluminum, Overdrive 1½ - 1⅝" head tube, integrated KS18 kickstand mount
- Fork: RST Volante TNL coil, 60mm travel, tapered steerer, hydraulic lockout
- Shifters: Shimano SL-M2000
- Crankset: Forged Alloy minimal Q-factor, 36/48T
- Colors: Matte Black / Red

GEOMETRY

FRAME	S	M	L	XL
Seat Tube Length (mm)	435	485	535	585
Seat Tube Angle	74.0°	73.0°	73.0°	73.0°
Top Tube Length (mm)	570	590	610	630
Head Tube Length (mm)	130	140	155	170
Head Tube Angle	69.5°	69.5°	69.5°	69.5°
Fork Rake (mm)	42	42	42	42
Trail (mm)	91.3	91.3	91.3	91.3
Wheelbase (mm)	1112	1121	1142	1163
Chain Stay Length (mm)	455	455	455	455
Bottom Bracket Drop (mm)	60	60	60	60
Stack (mm)	610	619	633	648
Reach (mm)	395	400	416	432
Stand Over Height (mm)	745	775	808	844
Handlebar Width (mm)	690	690	690	690
Stem Length (mm)	60	70	80	90
Crank Length (mm)	170	170	170	170
Wheel Size	700c	700c	700c	700c

The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city / country.