

FATHOM E+ 3 POWER



SPECS

FRAME	
SIZES	XS, S, M, L, XL
COLORS	Matte Black / Silver
FRAME	ALUXX aluminum, Overdrive 1½ - 1⅞" head tube, 141mm Boost QR, integrated KS18 kickstand mount
FORK	SR Suntour XCM 32 NLO DS 15AH-110, 27.5 120mm travel, Tapered 1½ - 1⅞" steerer, lockout
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Connect TR Riser 31.8x750mm
STEM	Giant Contact
SEATPOST	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SADDLE	Giant Sport
PEDALS	Aluminum Platform
DRIVETRAIN	
SHIFTERS	Shimano SL-M2000
FRONT DERAILLEUR	-
REAR DERAILLEUR	Shimano Deore, 9-Speed, Shadow design
BRAKES	Tektro HD-M285, hydraulic disc, 180mm
BRAKE LEVERS	Tektro HD-M285
CASSETTE	Shimano CS-HG200, 11-36T, 9-Speed
CHAIN	KMC e.9 Sport
CRANKSET	Forged Alloy minimal Q-factor, 36T Steel Direct Mount ring
WHEELS	
BOTTOM BRACKET	N/A
RIMS	Giant AM 27.5, Tubeless ready, 30mm inner width
HUBS	Giant eTracker Sport, [F] 15mm Thru-Axle [R] 141mm QR
SPOKES	Stainless steel
TIRES	Maxxis Forekaster 27.5x2.6, foldable, 60 TPI, EXO, Tubeless ready
EXTRAS	Giant EnergyPak 4A fast charger
HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport
SENSORS	Giant PedalPlus 6-sensor technology
DISPLAY	Giant RideControl ONE
BATTERY	Giant EnergyPak500, 36V 13.8Ah Rechargeable Lithium-Ion

FEATURES

- Frame: ALUXX aluminum, Overdrive 1½ - 1⅞" head tube, 141mm Boost QR, integrated KS18 kickstand mount
- Fork: SR Suntour XCM 32 NLO DS 15AH-110, 27.5 120mm travel, Tapered 1½ - 1⅞" steerer, lockout
- Shifters: Shimano SL-M2000
- Crankset: Forged Alloy minimal Q-factor, 36T Steel Direct Mount ring
- Colors: Matte Black / Silver

GEOMETRY

FRAME	XS	S	M	L	XL
Seat Tube Length (mm)	365	405	455	505	535
Seat Tube Angle	73.0°	73.0°	73.0°	73.0°	73.0°
Top Tube Length (mm)	555	575	595	615	635
Head Tube Length (mm)	110	110	115	140	150
Head Tube Angle	68.0°	68.0°	68.0°	68.0°	68.0°
Fork Rake (mm)	46	46	46	46	46
Trail (mm)	100.7	100.7	100.7	100.7	100.7
Wheelbase (mm)	1115	1135	1156	1178	1199
Chain Stay Length (mm)	470	470	470	470	470
Bottom Bracket Drop (mm)	45	45	45	45	45
Stack (mm)	617	617	622	645	654
Reach (mm)	366	386	405	417	435
Stand Over Height (mm)	737	753	760	787	791
Handlebar Width (mm)	780	780	780	780	780
Stem Length (mm)	50	50	60	60	70
Crank Length (mm)	165	165	170	170	170
Wheel Size	27.5+	27.5+	27.5+	27.5+	27.5+

The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city / country.