

AVOW ADVANCED PRO 1



Sonderbestellung bis 16.08. mit LT März 2020

SPECS

FRAME	
SIZES	XS, S, M
COLORS	Metallic Red
FRAME	Advanced-Grade Composite
FORK	Advanced-Grade Composite, alloy OverDrive steerer
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Liv Avow, carbon base bar
STEM	Avow, alloy
SEATPOST	Avow, composite
SADDLE	ISM PS1.0
PEDALS	N/A
DRIVETRAIN	
SHIFTERS	Shimano Ultegra Di2
FRONT DERAILLEUR	Shimano Ultegra Di2
REAR DERAILLEUR	Shimano Ultegra Di2
BRAKES	Giant SpeedControl SL
BRAKE LEVERS	Giant Trinity
CASSETTE	Shimano Ultegra, 11x30
CHAIN	KMC X11SL-1
CRANKSET	Shimano Ultegra 34/50, Giant Power Pro power meter
WHEELS	
BOTTOM BRACKET	Shimano, press fit
RIMS	Giant P-A2 wheelset
HUBS	Giant P-A2 wheelset
SPOKES	Giant P-A2 wheelset
TIRES	Giant Gavia Fondo 1, 700x32, tubeless
EXTRAS	integrated hydration, integrated food storage, AeroVault system

FEATURES

- Frame: Advanced-Grade Composite
- Fork: Advanced-Grade Composite, alloy OverDrive steerer
- Shifters: Shimano Ultegra Di2
- Crankset: Shimano Ultegra 34/50, Giant Power Pro power meter
- Colors: Metallic Red

GEOMETRY

FRAME	XXS	XS	S	M
Seat Tube Length (mm)	450	480	510	530
Seat Tube Angle	77.0°	77.0°	77.0°	77.0°
Top Tube Length (mm)	480	500	515	540
Head Tube Length (mm)	80	80	95	125
Head Tube Angle	71.5°	72.0°	72.5°	72.5°
Fork Rake (mm)	40	40	40	40
Trail (mm)	62	68	64	64
Wheelbase (mm)	949	961	974	1001
Chain Stay Length (mm)	405	405	405	405
Bottom Bracket Drop (mm)	64	75	75	75
Stack (mm)	442	490	504	534
Reach (mm)	378	387	398	417
Stand Over Height (mm)	708	740	767	788
Handlebar Width (mm)	400	400	400	400
Stem Length (mm)	80	80	80	80
Crank Length (mm)	160	160	165	165
Wheel Size	F650C/R700C	700C	700C	700C

The specifications, colors, and availability of the products can be subjects to alter without prior notification. For availability and prices, please contact the retailers in your city / country.